


D3

Patent Abstracts of Japan

PUBLICATION NUMBER : JP10189038
 PUBLICATION DATE : 21-07-98
 APPLICATION NUMBER : JP960346238
 APPLICATION DATE : 25-12-96

VOL: 98 NO: 12 (-)
 AB. DATE : 31-10-1998 PAT: A 10189038
 PATENTEE : MITSUI CHEM INC
 PATENT DATE: 21-07-1998



INVENTOR : HIBARA AKIO;
 ONOMI TAKEHIKO

INT.CL. : H01M10/40

TITLE : NONAQUEOUS ELECTROLYTE AND
 NONAQUEOUS ELECTROLYTIC
 SECONDARY BATTERY

ABSTRACT : PROBLEM TO BE SOLVED: To provide a nonaqueous electrolytic secondary battery having a high degree of incombustibility and safety, having the capability of generating high voltage and further having a high charging and discharging function by composting a nonaqueous electrolyte of a nonaqueous solvent containing a phosphoric ester compound having a group with an ether linkage and an electrolyte.

SOLUTION: The nonaqueous electrolyte of a secondary battery is composed of a nonaqueous solvent containing the phosphoric ester compound expressed by the formula and an electrolyte. In the formula, R<1> , R<2> and R<3> may be identical to or different from each other, and are an alkyl group having carbons between 1 and 4, or a group having the ~~ether linkage~~ expressed by -R<4> -O-R<5> . Also, R<4> and R<5> stand for a hydrocarbon group having carbons between 1 and 10. Furthermore, lithium salt such as LiPF₆ , LiBF₄ , LiClO₄ , LiAsF₆ , and LiCF₃ SO₃ is mentioned, for example, as an electrolyte dissolved in the nonaqueous electrolyte. Also, the electrolyte is preferably contained in the nonaqueous electrolyte at a level of concentration between 0.5 and 2mol/L. The nonaqueous electrolyte may be used for a cylindrical nonaqueous electrolytic secondary battery or the like